VESPA RIDING ACROSS TUSCANY

Your Vespa is waiting for you... San Cerbone's Cathedral in Massa Marittima. A winter sunset on the Etruscan coast Gently hills in the pisan countryside



Etruscan coast

Discover the beauty of the Tuscan countryside riding a Vespa throughout one of the most fascinating areas of Tuscany. You will drive amidst the hills south of Pisa and have the chance to do an unusual tour, in an unspoilt area away from the main touristc trails. You will lose yourself in the wild nature of the unforgettable landscapes of the Cecina Valley, and have the chance of a breathtaking view from the fascinating town of Volterra, rich in Roman and Etruscan funds.

Enjoy the beauty of the 'Etruscan Coast', riding the 'Wine Road' crossing the land of great famous Tuscan Wines, such as the legendary Sassicaia. Discover the tiny village of Bolgheri and let the typical vegetation of Tuscan inland (wineyards, olive-trees, cypresses) be Your companion for a while as far as the unspoiled area of Val di Cornia: there, in the hilly Etruscan territory south of Livorno, You will find landscape of unusual wild beauty and enchanted beaches, such as the one at the lovely Baratti Gulf.





E DAY ONE

DAY ONE
PISAN HILLS AND LIVORNO CLIFFS
Itinerary N°1 Km 130,35:
A vespa-ride through the beautiful hills of the Pisan area, discovering villages such as Guardistallo or Pomaia, in a gently sloping panorama. As you approach the coast colours and air perfumes change completely, till the 'Thyrrenean Pearl', Castiglioncello. This well-known holiday resort has its own particular charm. Sheer red cliffs, sheltered bays, bathing beaches and course washed by spretch clear water together with a shady pinewood. coves washed by crystal clear water, together with a shady pinewood.



DAY TWO DISCOVERING VAL DI CORNIA

Itinerary N°2 Km 126,20:

Our itinerary will lead you in the farthest southern part of the Livorno region, out of the croudy seaside resorts, and reveals the beauty of the Val di Cornia, which takes its name from the river that flows in its middle. You'll than reach 2 medieval "pearls" of the province of Grosseto: Monterotondo and Massa Marittima. This area is covered by olive groves and woods of oaks, beech trees and limes which provide the ideal environment for many animal species, and gives us the chance of a unique ride in the wild nature, away from the touristic trails.



DAY THREE VISITING VOLTERRA AND CECINA VALLEY

Itinerary N°3 Km 147,90:

An itinerary in the unspoiled nature of the Cecina Valley, where a scenic landscape betrays the presence of ancient settlements, castles, villages and churches. One of the most beautiful towns of Tuscany waits to be discovered on the top of a hill: this is Volterra, a haven of Etruscan, Roman, Medieval and Renaissance art, which dominates the Cecina Valley, offering spectacular views.



TASTING DAY

The area between Castagneto Carducci and Bolgheri is an ideal place for growing grapes and olives, because of the configuration of the terrain and the nearness to the sea. Hills covered in vineyards and olive groves so close to the Thyrrhenian Sea, make this land rich, and thanks to the mild climate and perfect position one of the finest wines from the Maremma coast is produced here "Sassicaia".

The Oil

Specializing in olive growing since it was founded Olive Farm is situated on the hills of Segalari, half way between Castagneto Carducci and Bolgheri.

The entire productive cycle is carried out here, from growing the olives to bottling



the finished product, oil. The greatest advantage of this company is that they have their own olive mill (since 2001 they are equipped for producing "denocciolato" or "stoneless" which is an oil obtained from just the flesh of the olive without the stone, therefore less acidic and with a milder flavor). All phases of oil production are carried out with the greatest speed and most careful attention, thus obtaining a high quality oil as required by the IGP certification.

The Wine

The history of wine, its heady aroma and flavor died out with the memories of the noble families of the Gherardesca, only to reappear in our days praised by the Poet Carducci who so loved to enjoy the sweet nectar. The wine company is



situated on the hills between Castagneto Carducci and Bolgheri, at a height of 100 meters above sea level, 9 hectares of vineyards are organically farmed.

The wine is made according to the traditional methods the natural slope of the land is made use of and therefore there is little need for pumps. Wooden casks are utilized for making the wine, refining the taste and controllingthe temperature and humidity required for the aging process.

The Vespa will continue to be your vehicle to reach designated vineyards for wine tasting by yourself, you will have however to keep up with timetables. The road book will guide



you firstly to a frantoio (the mill where oil is produced by crushing and pressing olives) and then to the vineyards (villas for wine tasting).



The **Vespa LX** offers a blend of classic style, round headlamp and rearview mirrors in chrome-plated steel are a style statement straight out of Vespa history, and sharp edge modern design. The all-steel body sets the Vespa LX apart from any other scooter produced today and offers unmatchable rigidity and steering precision. The saddle height gives riders of any height perfect control of the vehicle and the 11inch front wheel

Displacement124,02 ccBore57 mmStroke48,6 mmMax Power7.6 Kw (10.3 bhp) at 8,000 rpmMax Torque9.6 Nm at 6,000 rpmFuelUnleaded petrol N.O.R. min. 95InductionSOHCIgnitionElectronic CDI and variable timingStarterElectric and kick starterLubricationWet pump with cup capacity of 1 litre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueOscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront tyreTubeless 110/70 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10"Front tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		1
Bore57 mmStroke48,6 mmMax Power7.6 Kw (10.3 bhp) at 8,000 rpmMax Torque9.6 Nm at 6,000 rpmFuelUnleaded petrol N.O.R. min. 95InductionSOHCIgnitionElectronic CDI and variable timingStarterElectric and kick starterLubricationWet pump with cup capacity of 1 litre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueScillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Engine	LEADER 4 stroke, single cylinder
Stroke48,6 mmMax Power7.6 Kw (10.3 bhp) at 8,000 rpmMax Torque9.6 Nm at 6,000 rpmFuelUnleaded petrol N.O.R. min. 95InductionSOHCIgnitionElectronic CDI and variable timingStarterElectric and kick starterLubricationWet pump with cup capacity of 1 litre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGoscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionMelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11" Rear wheel rimRear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Displacement	
Max Power7.6 Kw (10.3 bhp) at 8,000 rpmMax Torque9.6 Nm at 6,000 rpmFuelUnleaded petrol N.O.R. min. 95InductionSOHCIgnitionElectronic CDI and variable timingStarterElectric and kick starterLubricationWet pump with cup capacity of 1Iitre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGoscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront tyreTubeless 110/70 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10" LengthLength1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mm Dry weightDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		
Max Torque 9.6 Nm at 6,000 rpm Fuel Unleaded petrol N.O.R. min. 95 Induction SOHC Ignition Electronic CDI and variable timing Starter Electric and kick starter Lubrication Wet pump with cup capacity of 1 litre, chain driven lobe pump Cooling Forced air Gear change Automatic CVT with torque server Clutch Automatic centrifuge type Frame Pressed steel monocoque Goscillating arm with helicoidal spring and hydraulic double effect single damper Rear suspension Helicoidal adjustable spring and hydraulic double effect single damper Front brake Ø 200 mm stainless steel disc with dual piston hydraulic calliper Ø 200 mm drum, mechanically commanded Commanded Front wheel rim Die-cast aluminium alloy, 2.50 - 11" Rear wheel rim Die-cast aluminium alloy, 3.00 - 10" Length 1,800 mm Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm </th <th>Stroke</th> <th>48,6 mm</th>	Stroke	48,6 mm
FuelUnleaded petrol N.O.R. min. 95InductionSOHCIgnitionElectronic CDI and variable timingStarterElectric and kick starterLubricationWet pump with cup capacity of 1litre, chain driven lobe pumpCoolingCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGoscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Max Power	7.6 Kw (10.3 bhp) at 8,000 rpm
InductionSOHCIgnitionElectronic CDI and variable timingStarterElectric and kick starterLubricationWet pump with cup capacity of 1 litre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGoscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and 	Max Torque	9.6 Nm at 6,000 rpm
IgnitionElectronic CDI and variable timing StarterStarterElectric and kick starterLubricationWet pump with cup capacity of 1 litre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGoscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		
StarterElectric and kick starterLubricationWet pump with cup capacity of 1 litre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGoscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		
LubricationWet pump with cup capacity of 1 litre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGoscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		
Lubricationlitre, chain driven lobe pumpCoolingForced airGear changeAutomatic CVT with torque serverClutchAutomatic centrifuge typeFramePressed steel monocoqueGront suspensionOscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Starter	
Gear change Automatic CVT with torque server Clutch Automatic centrifuge type Frame Pressed steel monocoque Goscillating arm with helicoidal spring and hydraulic double effect single damper Rear suspension Helicoidal adjustable spring and hydraulic double effect single damper Front brake Ø 200 mm stainless steel disc with dual piston hydraulic calliper Rear brake Ø 110 mm drum, mechanically commanded Front wheel rim Die-cast aluminium alloy, 2.50 - 11" Rear tyre Tubeless 110/70 - 11" Rear tyre Tubeless 120/70 - 10" Length 1,800 mm Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres		litre, chain driven lobe pump
Clutch Automatic centrifuge type Frame Pressed steel monocoque Scillating arm with helicoidal spring and hydraulic double effect single damper Rear suspension Helicoidal adjustable spring and hydraulic double effect single damper Front brake Ø 200 mm stainless steel disc with dual piston hydraulic calliper Rear brake Ø 110 mm drum, mechanically commanded Front wheel rim Die-cast aluminium alloy, 2.50 - 11" Rear tyre Tubeless 110/70 - 11" Rear tyre Tubeless 120/70 - 10" Length 1,800 mm Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm		
FramePressed steel monocoqueFront suspensionOscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10"Front tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		
Front suspensionOscillating arm with helicoidal spring and hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10"Front tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Clutch	
Front suspensionand hydraulic double effect single damperRear suspensionHelicoidal adjustable spring and hydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10"Front tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Frame	Pressed steel monocoque
Rear suspensionhydraulic double effect single damperFront brakeØ 200 mm stainless steel disc with dual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10"Front tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Front suspension	
Front brakedual piston hydraulic calliperRear brakeØ 110 mm drum, mechanically commandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10"Front tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Rear suspension	hydraulic double effect single
Rear brakecommandedFront wheel rimDie-cast aluminium alloy, 2.50 - 11"Rear wheel rimDie-cast aluminium alloy, 3.00 - 10"Front tyreTubeless 110/70 - 11"Rear tyreTubeless 120/70 - 10"Length1,800 mmWidth740 mmWheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm	Front brake	dual piston hydraulic calliper
Rear wheel rim Die-cast aluminium alloy, 3.00 - 10" Front tyre Tubeless 110/70 - 11" Rear tyre Tubeless 120/70 - 10" Length 1,800 mm Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm		commanded
Front tyre Tubeless 110/70 - 11" Rear tyre Tubeless 120/70 - 10" Length 1,800 mm Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm		
Rear tyre Tubeless 120/70 - 10" Length 1,800 mm Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm		Die-cast aluminium alloy, 3.00 - 10"
Length 1,800 mm Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm		
Width 740 mm Wheel base 1,280 mm Saddle height 775 mm Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm		
Wheel base1,280 mmSaddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm)
Saddle height775 mmDry weight110 kgFuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		740 mm
Dry weight 110 kg Fuel tank cap. 8,6 litres Power CV 12 (Kw 8.8) at 8,000 rpm		·
Fuel tank cap.8,6 litresPowerCV 12 (Kw 8.8) at 8,000 rpm		-
Power CV 12 (Kw 8.8) at 8,000 rpm		110 kg
		- ,
Maximum speed 91 Km/hour	Maximum speed	91 Km/hour

guarantees greater stability and pinpoint steering. The braking system, powerful 200mm front disc brake, ensures stability and a smooth ride.





PHOTOS: Vespa LX 125cc. CHART: Vespa-Technical information

Your bike





Versiliana Viaggi di Vita Toscana S.r.I. Via Padre Eugenio Barsanti, 63-65 55045 Pietrasanta (LU) - P.IVA: 01575150469 Tel. 0584-36541 - Fax 0584-365430 -E-mail: info@versilianaviaggi.it - www.versilianaviaggi.it Tour designer, Vespa hire and technical support by:

Organized by:

ECO-RENT di Papini Daniele Via Tosco Romagnola, 1321 56023 - San Casciano di Cascina (PI) Italy Tel +39 050 777461 - Fax +39 050 6140064 E-mail: info@ecorent.net - www.ecorent.net